

## RPM Speedway Figure 8

1. **Safety-** Five point safety belts fastened to roll cage, racing seats also fastened to roll cage, SFI approved fire suit, Snell SA 85 racing helmets, fire retardant gloves and neck brace, racing fuel cell with check valve, fuel cell must be mounted to frame, fuel lines running through drivers compartment must be inside steel pipe or conduit. Drive shaft must be painted white. A 360 degree drive shaft loop of at least  $\frac{1}{4}$  inch X 2 inch steel mounted 6 inches back of front u-joint. Must have window nets. Roll bar padding required.
2. **Roll Cage-** A full perimeter four post roll cage welded to frame, three horizontal door bars on drivers door and must be plated. There must be one cross bar in top halo. Rear hoop must be X braced. Minimum of 1  $\frac{1}{2}$  tubing. Minimum of three windshield bars in front of each driver.
3. **Body-** Only cutting allowed is for placement of roll cage and front fender wells. Doors must be securely fastened, trunk and hood must have at least two hood pins. Must have 18 inch lettering on doors and hood. Must remove all chrome, plastic, pot metal, fiberglass, lights, glass, and trash. No mirrors. No ballast.
4. **Wheelbase-** Minimum of 112 inches.

5. **Battery**-Securely fastened and covered.
6. **Bumpers**- OEM for the make of car you're using. No extra reinforcement. Factory mounts may be welded.
7. **Brakes**- OEM on all four wheels and working. OEM brake pedals and master cylinder in stock location
8. **Suspension**- Must have OEM shocks and springs. No heating or cutting of springs. NO spacers, chains, lumber, weight jacks, or adaptors allowed.
9. **Steering**-OEM steering only in stock location.
10. **Wheels and Tires**- Any DOT tire up to 60 series. Minimum air pressure on each tire, 28 lbs. Maximum 8 inch steel wheels. 1 inch lug nuts
11. **Engine**- OEM engines only. No aluminum heads, water pumps, or blocks. No headers. OEM ignition only. Must idle smooth at 800 rpm and hold 15 inches of vacuum.
12. **Carburetor**- OEM unaltered carburetor only.
13. **Transmission**- OEM automatic only with working torque convertor.
14. **Rearends**- OEM rear ends only
15. **Decisions of track officials are final.** If it doesn't say you can, you can't!